



**Spirex**  
Safety technologies

[www.spirex.es](http://www.spirex.es)

## **VESTUARIO DE PROTECCIÓN DE USO LIMITADO**

GAMA COMPLETA DE VESTUARIO DESECHABLE DE  
PROTECCIÓN QUÍMICA, BIOLÓGICA Y PARTÍCULAS NOCIVAS



**RSG**<sup>®</sup>  
TOTAL RESPIRATORY



**TRUST BUILT**

**UPON RELIABILITY**



**T-Air**<sup>®</sup>

RESPIRATORY AIRLINE RANGE

## HEADTOPS AND HOOD OPTIONS



### T-AIRLINE 1000 M

Part # 614050

- Hood made of Microporous film laminate with overpressure valve
- Includes RSG unique airflow indicator for low flow warning
- Easy adjustable head harness with ratchet Chemical resistant PETG visor
- Comfortable SMS neck seal

EN14594:2005 Class  
3B/4A (NPF 2000)



### T-AIRLINE 1000 CHEM1

Part # 614051

- Hood made of HDPE barrier film laminate with overpressure valve
- Easy adjustable and reusable head harness with ratchet
- Chemical resistant PETG visor
- Includes RSG unique airflow indicator for low flow warning
- Comfortable SMS neck seal

EN14594:2005 Class  
3B/4A (NPF 2000)



### T-AIRLINE 1000 CHEM3

Part # 614052

- Hood made of Multi-layer composite material with EVOH film barrier with exhalation valve
- Includes RSG unique airflow indicator for low flow warning
- Easy adjustable and reusable head harness with ratchet
- Chemical resistant PETG visor
- Comfortable SMS neck seal

EN14594:2005 Class  
3B/4A (NPF 2000)



### T-AIRVISOR

Part # 614100

- Large viewing area, chemical and mechanical resistant visor
- Easy removal disposable visor system
- Possibility to flip up visor
- Comfortable elastic cotton face seal
- Includes RSG unique airflow indicator for low flow warning
- Easy adjustable head harness with ratchet

EN14594:2005 Class  
3B (NPF 200)



## AIRLINE FILTER UNIT

Code: 600161 / 600162 / 600163 / 600164

- Breathing Air according EN12021:1999 offering clean, particle and oil free air
- Wall or floor mounted to suit 2 and 4 users
- 2 stage high dirt holding capacity 0.01 micron rated filter to remove particles and oil aerosol to 0.003 mg/m<sup>3</sup>.
- Activated carbon filter to remove odours and vapours



The headtops are approved to EN14594:2005 Class 3B/4A and provide protection for eye, face, neck and shoulders. The T-AirLine series headtops offer lightweight and comfortable protection in many industrial applications.



## T-AIRWELD 820

Part # 614210

- Respiratory (EN14594) and eye protection (EN175B)
- High quality ADF lens with 4 sensors, 9x13 variable for welding / grinding, optical class 1/2/1/1
- Viewing area 95 x 85 mm
- Possibility to flip up visor
- Comfortable elastic cotton face seal
- Easy adjustable head harness with ratchet
- Strong and flexible PE breathing hose
- Includes RSG unique airflow indicator for low flow warning
- Comfortable easy to adjust airflow

EN14594:2005 Class 3B (NPF 200)



Grinding / Welding



## T-AIRWELD 500

Part # 614200 / 614201

- Respiratory (EN14594) and eye protection (EN175B)
- The T-AirWeld 500 can be equipped either with a fixed shade welding lens flip up or ADF.
- Optional ADF lens with 2 sensors, 9-13 adjustable for welding / grinding, optical class 1/3/1/2
- Viewing area of 96 x 42 mm
- Possibility to flip up visor
- Comfortable elastic cotton face seal
- Adjustable head harness with ratchet
- Includes RSG unique airflow indicator for low flow warning
- Comfortable, easy to adjust airflow regulator

EN14594 Class 3B (NPF200)



Grinding / Welding



## UNIQUE AIRFLOW INDICATOR

The Unique RSG airflow indicator provides optical indication and warning for low flow. In case of any air supply problems (<170l/min) the user will be warned immediately.



## T-AIRLINE REGULATOR

Code: 661368

- Slim, safe and simple to operate.
- Precisely adjustable airflow (between 180-350 litres).
- Supplied with in-line charcoal filter, for taste and odour removal for improved user comfort and performance.
- CEJN nipple, HDPE breathing hose. 40mm black PE belt.
- EN approved with all RSG T-AirLine hoods according EN14594 class 3B/4A.

## HOSE OPTIONS

Code: 661250 / 661252 / 661253

- Tested and approved with T-AirLine Filter Units, Regulator and all T-AirLine headtops.
- All hoses fulfil the test procedures of the EN14593 & EN14594:2005 class A and B.
- Fitted with CEJN double action safety coupling and nipple for ease of use and safe (dis)connection.
- Range of Light duty PVC plastic hoses, 10 and 20 meter and Heavy duty anti-static, heat resistant and flame retardant chemical resistant rubber hoses, 10, 20 and 30 meter.
- Flexible spiral PU hoses in 2, 4, 6 and 8 meters.

**TRUST BUILT**

**UPON RELIABILITY**



**RSG Safety BV**

**Marinus Dammeweg 38  
5928 PW Venlo, The Netherlands**

**Tel: +31 (0)85 487 0395  
E-mail: [sales@rsgsafety.com](mailto:sales@rsgsafety.com)**

**[www.rsgsafety.com](http://www.rsgsafety.com)**